API NUMBER: 011 24037

Oil & Gas

Horizontal Hole

## OKLAHOMA CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION P.O. BOX 52000 OKLAHOMA CITY, OK 73152-2000 (Rule 165:10-3-1)

Approval Date: 06/21/2018

Expiration Date: 12/21/2018

PERMIT TO DRILL

WELL LOCATION:	Sec:	02	Twp:	16N	Rge:	10W	County:	BLAINE
----------------	------	----	------	-----	------	-----	---------	--------

SPOT LOCATION: SW NW NE NW FEET FROM QUARTER: FROM NORTH FROM WEST SECTION LINES: 495 1405

Lease Name: CASTONGUAY Well No: 1610 3H-2X Well will be 495 feet from nearest unit or lease boundary.

Operator NEWFIELD EXPLORATION MID-CON INC Telephone: 2816742521; 9188781 OTC/OCC Number: 20944 0

NEWFIELD EXPLORATION MID-CON INC 24 WATERWAY AVE STE 900

THE WOODLANDS, TX 77380-2764

JDN FAMILY TRUST, DONNA MCCREIGHT TRUSTEE 126 S. BREEZY POINT CIRCLE

WICHITA KS 66235

Formation(s) (Permit Valid for Listed Formations Only):

Name Depth Name Depth MISSISSIPPIAN 1 9296 6 2 WOODFORD 9916 7 3 8 4 9 5 10 646685 Spacing Orders: Location Exception Orders: Increased Density Orders: 679348 647101 679347

Pending CD Numbers: 201803121 Special Orders:

201803122

Total Depth: 19965 Ground Elevation: 1239 Surface Casing: 1500 Depth to base of Treatable Water-Bearing FM: 90

Under Federal Jurisdiction: No Fresh Water Supply Well Drilled: No Surface Water used to Drill: Yes

H. SEE MEMO

PIT 1 INFORMATION Approved Method for disposal of Drilling Fluids:

Type of Pit System: CLOSED Closed System Means Steel Pits

Type of Mud System: WATER BASED
Chlorides Max: 8000 Average: 5000

Is depth to top of ground water greater than 10ft below base of pit? Y

Within 1 mile of municipal water well?

within i fille of fluricipal water well?

Wellhead Protection Area? N

Pit is not located in a Hydrologically Sensitive Area.

Category of Pit: C

**Liner not required for Category: C**Pit Location is NON HSA

Pit Location Formation: FLOWERPOT

E. Haul to Commercial pit facility: Sec. 31 Twn. 12N Rng. 8W Cnty. 17 Order No: 587498

## PIT 2 INFORMATION

Type of Pit System: CLOSED Closed System Means Steel Pits

Type of Mud System: OIL BASED Chlorides Max: 300000, Average: 200000

Is depth to top of ground water greater than 10ft below base of pit? Y

Within 1 mile of municipal water well? N Wellhead Protection Area?

Pit is not located in a Hydrologically Sensitive Area.

Category of Pit: C

Liner not required for Category: C Pit Location is NON HSA

Pit Location Formation: FLOWERPOT

## **HORIZONTAL HOLE 1**

Sec. 11 Twp 16N Rge 10W County **BLAINE** Spot Location of End Point: SW SW SF SW Feet From: SOUTH 1/4 Section Line: 85 Feet From: WEST 1/4 Section Line: 1578

Depth of Deviation: 9161 Radius of Turn: 477 Direction: 178

Total Length: 10055

Measured Total Depth: 19965 True Vertical Depth: 9916 End Point Location from Lease, Unit, or Property Line: 85

Notes:

Category Description

**DEEP SURFACE CASING** 6/14/2018 - G71 - APPROVED; NOTIFY OCC FIELD INSPECTOR IMMEDIATELY FOR ANY LOSS

OF CIRCULATION OR FAILURE TO CIRCULATE CEMENT TO SURFACE ON CONDUCTOR OR

SURFACE CASING

HYDRAULIC FRACTURING 6/14/2018 - G71 - OCC 165:10-3-10 REQUIRES:

> 1) PRIOR TO COMMENCEMENT OF HYDRAULIC FRACTURING OPERATIONS FOR HORIZONTAL WELLS, NOTICE GIVEN FIVE BUSINESS DAYS IN ADVANCE TO OFFSET OPERATORS WITH WELLS COMPLETED IN THE SAME COMMON SOURCE OF SUPPLY WITHIN 1/2 MILE:

2) WITH NOTICE ALSO GIVEN 48 HOURS IN ADVANCE OF HYDRAULIC FRACTURING ALL WELLS TO BOTH THE OCC CENTRAL OFFICE AND LOCAL DISTRICT OFFICES, USING THE

"FRAC NOTICE FORM" FOUND AT THE FOLLOWING LINK:

OCCEWEB.COM/OG/OGFORMS.HTML; AND,

3) THE CHEMICAL DISCLOSURE OF HYDRAULIC FRACTURING INGREDIENTS FOR ALL WELLS TO BE REPORTED TO FRACFOCUS WITHIN 60 DAYS AFTER THE CONCLUSION THE

HYDRAULIC FRACTURING OPERATIONS, USING THE FOLLOWING LINK: FRACFOCUS.ORG

6/19/2018 - G75 - 2-16N-10W **INCREASED DENSITY - 679347** 

X646685 MSSP 9 WELLS

NEWFIELD EXPLOR. MID-CONT. INC.

6-18-2018

**INCREASED DENSITY - 679348** 6/19/2018 - G75 - 11-16N-10W

X647101 MSSP 9 WFIIS

NEWFIELD EXPLOR. MID-CONT. INC.

6-18-2018

Category Description

INTERMEDIATE CASING 6/14/2018 - G71 - DUE TO THE KNOWN POTENTIAL RISK OF ENCOUNTERING AN OVER-

PRESSURED ZONE IN THE MORROW SERIES IN THIS AREA, THE TECHNICAL MANAGER RECOMMENDS SETTING AN INTERMEDIATE STRING OF CASING IMMEDIATELY ABOVE THE

MORROW SERIES

MEMO 6/14/2018 - G71 - PIT 1 & 2 - CLOSED SYSTEM = STEEL PITS PER OPERATOR REQUEST; WBM,

WBM & OBM CUTTINGS CAPTURED IN STEEL HALF PITS & TRANSFERRED TO R360 (ORDER

#587498); PIT 2 - OBM TO VENDOR

PENDING CD - 201803121 6/20/2018 - G75 - (I.O.) 2 & 11-16N-10W

EST MULTIUNIT HORÍZONTAL WELL X646685 MSSP, WDFD 2-16N-10W X647101 MSSP, WDFD 11-16N-10W

(WDFD ADJACENT COMMON SOURCE OF SUPPLY TO MSSP)

50% 2-16N-10W 50% 11-16N-10W NO OP. NAMED REC 5-8-2018 (MURER)

PENDING CD - 201803122 6/20/2018 - G75 - (I.O.) 2 & 11-16N-10W

X646685 MSSP, WDFD 2-16N-10W X647101 MSSP, WDFD 11-16N-10W

COMPL. INT. (2-16N-10W) NCT 165' FNL, NCT 0' FSL, NCT 1320' FWL COMPL. INT. (11-16N-10W) NCT 0' FNL, NCT 165' FSL, NCT 1320' FWL

NO OP. NAMED REC 5-8-2018 (MURER)

PENDING CD - 201803129 6/19/2018 - G75 - (I.O.) 2 & 11-16N-10W

X165:10-3-28(C)(2)(B) MSSP (CASTONGUAY 1610 3H-2X) MAY BE CLOSER THAN 600' TO EXISTING/PROPOSED WELL

NEWFIELD EXPLOR. MID-CONT. INC.

REC 5-8-2018 (MURER)

SPACING - 646685 6/19/2018 - G75 - (640)(HOR) 2-16N-10W

EXT 639444 MSSP, WDFD, OTHER POE TO BHL (MSSP) NCT 660' FB

POE TO BHL (WDFD) NCT 165' FNL & FSL, NCT 330' FEL & FWL

(COEXIST SP. ORDER # 168134/169097 MSSSD & ORDER # 189055 MCSTR)

SPACING - 647101 6/19/2018 - G75 - (640)(HOR) 11-16N-10W

EXT 639444 MSSP, WDFD, OTHER POE TO BHL (MSSP) NCT 660' FB

POE TO BHL (WDFD) NCT 165' FNL & FSL, NCT 330' FEL & FWL

(COEXIST SP. ORDER # 168134/169097 MSSSD; ORDER # 189055 MCSTR; ORDER # 527546

MNNG SE4)

