API NUMBER: 051 24406 Α OKLAHOMA CORPORATION COMMISSION **OIL & GAS CONSERVATION DIVISION** P.O. BOX 52000 **OKLAHOMA CITY, OK 73152-2000** (Rule 165:10-3-1)

Approval Date: 07/12/2018 01/12/2019 **Expiration Date**

250 feet from nearest unit or lease boundary.

Depth

23914 0

OTC/OCC Number:

Horizontal Hole Oil & Gas

Lease Name: RAGSDALE

Amend reason: ADD FORMATION AND REVISE TD

AMEND PERMIT TO DRILL

Telephone: 5128140345

WELL LOCATION: Sec: Twp: 9N Rge: 6W County: GRADY FEET FROM QUARTER: WEST SPOT LOCATION: sw lsw FROM SOUTH FROM Isw IIsw SECTION LINES:

250 250

Well No:

1H-34

Operator

TRAVIS PEAK RESOURCES LLC Name:

BILL RAGSDALE

Name

178 COUNTY ROAD 1250

Well will be

TUTTLE OK 73089

TRAVIS PEAK RESOURCES LLC 9020 N CAPITAL OF TEXAS HWY BLDG 1 STE 170

AUSTIN. TX 78759-7279

Formation(s) (Permit Valid for Listed Formations Only):

Name Depth MISSISSIPPIAN 1 11090 6 2 WOODFORD 11160 7 3 HUNTON 11300 8 4 9 10

667608 Spacing Orders: Location Exception Orders: 681095 Increased Density Orders:

Pending CD Numbers: Special Orders:

Total Depth: 15900 Ground Elevation: 1251 Surface Casing: 1500 Depth to base of Treatable Water-Bearing FM: 290

Under Federal Jurisdiction: No Fresh Water Supply Well Drilled: No Surface Water used to Drill: Yes

Approved Method for disposal of Drilling Fluids: PIT 1 INFORMATION

Type of Pit System: CLOSED Closed System Means Steel Pits

Type of Mud System: WATER BASED H. SEE MEMO Chlorides Max: 5000 Average: 3000

Is depth to top of ground water greater than 10ft below base of pit? Y

Within 1 mile of municipal water well? N

Wellhead Protection Area?

located in a Hydrologically Sensitive Area.

Category of Pit: C

Liner not required for Category: C Pit Location is BED AQUIFER Pit Location Formation: DUNCAN D. One time land application -- (REQUIRES PERMIT) PERMIT NO: 18-34325

PIT 2 INFORMATION

Type of Pit System: CLOSED Closed System Means Steel Pits

Type of Mud System: OIL BASED
Chlorides Max: 300000 Average: 200000

Is depth to top of ground water greater than 10ft below base of pit? Y

Within 1 mile of municipal water well? N
Wellhead Protection Area? N

Pit is located in a Hydrologically Sensitive Area.

Category of Pit: C

Liner not required for Category: C
Pit Location is BED AQUIFER
Pit Location Formation: DUNCAN

HORIZONTAL HOLE 1

County Sec 34 Twp 9N Rge 6W **GRADY** Spot Location of End Point: NW ΝE ΝE NF Feet From: NORTH 1/4 Section Line: 50 EAST Feet From: 1/4 Section Line: 380

Depth of Deviation: 10690 Radius of Turn: 656 Direction: 355 Total Length: 4279

Measured Total Depth: 15900
True Vertical Depth: 11450
End Point Location from Lease,
Unit, or Property Line: 50

Notes:

Category Description

DEEP SURFACE CASING 7/5/2018 - G71 - APPROVED; NOTIFY OCC FIELD INSPECTOR IMMEDIATELY OF ANY LOSS OF

CIRCULATION OR FAILURE TO CIRCULATE CEMENT TO SURFACE ON ANY CONDUCTOR OR

SURFACE CASING

HYDRAULIC FRACTURING 7/5/2018 - G71 - OCC 165:10-3-10 REQUIRES:

1) PRIOR TO COMMENCEMENT OF HYDRAULIC FRACTURING OPERATIONS FOR HORIZONTAL WELLS, NOTICE GIVEN FIVE BUSINESS DAYS IN ADVANCE TO OFFSET OPERATORS WITH WELLS COMPLETED IN THE SAME COMMON SOURCE OF SUPPLY WITHIN 1/2 MILE:

2) WITH NOTICE ALSO GIVEN 48 HOURS IN ADVANCE OF HYDRAULIC FRACTURING ALL WELLS TO BOTH THE OCC CENTRAL OFFICE AND LOCAL DISTRICT OFFICES, USING THE

"FRAC NOTICE FORM" FOUND AT THE FOLLOWING LINK:

OCCEWEB.COM/OG/OGFORMS.HTML; AND,

3) THE CHEMICAL DISCLOSURE OF HYDRAULIC FRACTURING INGREDIENTS FOR ALL WELLS TO BE REPORTED TO FRACFOCUS WITHIN 60 DAYS AFTER THE CONCLUSION THE

HYDRAULIC FRACTURING OPERATIONS, USING THE FOLLOWING LINK: FRACFOCUS.ORG

LOCATION EXCEPTION - 681095 7/12/2018 - G58 - (I.O.) 34-9N-6W

X667608 MSSP, WDFD, HNTN

SHL 250' FSL, 250' FWL OF 35-9N-6W

COMPL. INT. NCT 150' FSL, NCT 150' FNL, NCT 330' FEL

TRAVIS PEAK RESOURCES LLC

8/7/2018

MEMO 7/5/2018 - G71 - PITS 1 & 2 - CLOSED SYSTEM=STEEL PITS PER OPERATOR REQUEST, PIT 2 -

OBM RETURNED TO VENDOR, CUTTINGS PERMITTED PER DISTRICT

Category Description

SPACING - 667608

7/12/2018 - G58 - (640)(HOR) 34-9N-6W EST MSSP, WDFD, HNTN COMPL. INT. (MSSP, HNTN) NLT 660' FB COMPL. INT. (WDFD) NLT 165' FNL & FSL, NLT 330' FEL & FWL (COEXIST SP. ORDER 217821 MSSLM, WDFD, HNTN)