

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35073252680000

Completion Report

Spud Date: April 04, 2016

OTC Prod. Unit No.: 073-217856-0-0000

Drilling Finished Date: April 18, 2016

1st Prod Date: September 16, 2016

Amended

Completion Date: September 11, 2016

Amend Reason: AMENDED TO ADD ACID & FRAC TREATMENT VOLUME

Drill Type: HORIZONTAL HOLE

Well Name: LANKARD 1706 6-34MH

Purchaser/Measurer:

Location: KINGFISHER 27 17N 6W
SE SE SW SE
270 FSL 1568 FEL of 1/4 SEC
Latitude: 35.91336 Longitude: -97.82353
Derrick Elevation: 0 Ground Elevation: 1057

First Sales Date:

Operator: OKLAHOMA ENERGY ACQUISITIONS LP 23509

15021 KATY FREEWAY STE 400
HOUSTON, TX 77094-1900

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	657372		There are no Increased Density records to display.	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
CONDUCTOR	16		X42	123		27	SURFACE
SURFACE	9 5/8	36	J55	476		300	SURFACE
INTERMEDIATE	7	26	P110	7709		280	4762

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4 1/2	13.5	P110	5171	0	0	7416	12587

Total Depth: 12588

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
7401	ASIII	There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Oct 15, 2016	MISS'AN (EX CHESTER)	1039	39	3519	3387	803	GAS LIFT		OPEN	298

Completion and Test Data by Producing Formation

Formation Name: MISS'AN (EX CHESTER)

Code: 359MSNLC

Class: OIL

Spacing Orders

Order No	Unit Size
652716	640

Perforated Intervals

From	To
There are no Perf. Intervals records to display.	

Acid Volumes

5873 BBLS 15% HCL ACID

Fracture Treatments

234,774 BBLS SLICKWATER 5,085,864# SAND PROPPANT

Formation	Top
COTTAGE GROVE	5733
HOGSHOOTER	5953
CHECKERBOARD	6052
CLEVELAND	6216
BIG LIME	6369
OSWEGO (4TH)	6512
PRUE	6579
VERDIGRIS	6618
SKINNER	6663
PINK LIME	6729
RED FORK	6765
INOLA	6809
MERAMEC	6956

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

10/13/17: AMENDED TO ADD ACID & FRAC TREATMENT VOLS (BH). THIS WELL IS AN OPEN HOLE COMPLETION FROM THE BOTTOM OF THE 7" CASING AT 7709' TO TERMINUS AT 12,588'. THE 4 1/2" LINER IS NOT CEMENTED. IRREGULAR SECTION.

Lateral Holes

Sec: 34 TWP: 17N RGE: 6W County: KINGFISHER

SW SW SE SE

207 FSL 1149 FEL of 1/4 SEC

Depth of Deviation: 6931 Radius of Turn: 894 Direction: 178 Total Length: 4457

Measured Total Depth: 12588 True Vertical Depth: 7450 End Pt. Location From Release, Unit or Property Line: 207