PI NUMBER: 051 24664 aight Hole Disposal	OIL & GAS (F OKLAHOI (I	CORPORATION COMMISS CONSERVATION DIVISION P.O. BOX 52000 MA CITY, OK 73152-2000 Rule 165:10-3-1)	
	<u>P</u>	ERMIT TO DRILL	
WELL LOCATION: Sec: 29 Twp: 6N Rge SPOT LOCATION: SW SE SE SW	SECTION LINES:	OUTH FROM WEST 37 2239	
Lease Name: BRAND SWD	Well No: 1	-29	Well will be 287 feet from nearest unit or lease boundary.
Operator S & S STAR OPERATING LLC Name:	2	Telephone: 4055296577	OTC/OCC Number: 23996 0
S & S STAR OPERATING LLC PO BOX 249	(70101 0010	WILLIAM 2971 COL	BRAND JNTY STREET 2940
OKLAHOMA CITY, OK	3101-0249	ALEX	OK 73002
Name 1 CHASE 2 DOUGLAS 3 4 5	Depth 4000 5500	Name 6 7 8 9 10	Depth
Spacing Orders: No Spacing	Location Exception Or	ders:	Increased Density Orders:
Pending CD Numbers:			Special Orders:
Total Depth: 6500 Ground Elevation	n: 1116 Surface Ca	asing: 410	Depth to base of Treatable Water-Bearing FM: 360
Under Federal Jurisdiction: No	Fresh Water St	upply Well Drilled: No	Surface Water used to Drill: No
		Approved Method for	disposal of Drilling Fluids:
PIT 1 INFORMATION		Approvod moniou ior	
PIT 1 INFORMATION Type of Pit System: ON SITE Type of Mud System: WATER BASED			ter and backfilling of reserve pit.
Type of Pit System: ON SITE Type of Mud System: WATER BASED Chlorides Max: 5000 Average: 3000			
Type of Pit System: ON SITE Type of Mud System: WATER BASED	ow base of pit? Y		
Type of Pit System: ON SITE Type of Mud System: WATER BASED Chlorides Max: 5000 Average: 3000 Is depth to top of ground water greater than 10ft bek	ow base of pit? Y		
Type of Pit System: ON SITE Type of Mud System: WATER BASED Chlorides Max: 5000 Average: 3000 Is depth to top of ground water greater than 10ft below Within 1 mile of municipal water well? N			
Type of Pit System: ON SITE Type of Mud System: WATER BASED Chlorides Max: 5000 Average: 3000 Is depth to top of ground water greater than 10ft below Within 1 mile of municipal water well? N Wellhead Protection Area? N Pit is located in a Hydrologically Sensitive Ar Category of Pit: 2			
Type of Pit System: ON SITE Type of Mud System: WATER BASED Chlorides Max: 5000 Average: 3000 Is depth to top of ground water greater than 10ft bek Within 1 mile of municipal water well? N Wellhead Protection Area? N Pit is located in a Hydrologically Sensitive Ar			

Notes:

HYDRAULIC FRACTURING

Description

6/27/2019 - G71 - OCC 165:10-3-10 REQUIRES:

1) PRIOR TO COMMENCEMENT OF HYDRAULIC FRACTURING OPERATIONS FOR HORIZONTAL WELLS, NOTICE GIVEN FIVE BUSINESS DAYS IN ADVANCE TO OFFSET OPERATORS WITH WELLS COMPLETED IN THE SAME COMMON SOURCE OF SUPPLY WITHIN 1/2 MILE;

2) WITH NOTICE ALSO GIVEN 48 HOURS IN ADVANCE OF HYDRAULIC FRACTURING ALL WELLS TO BOTH THE OCC CENTRAL OFFICE AND LOCAL DISTRICT OFFICES, USING THE "FRAC NOTICE FORM" FOUND AT THE FOLLOWING LINK: OCCEWEB.COM/OG/OGFORMS.HTML; AND,

3) THE CHEMICAL DISCLOSURE OF HYDRAULIC FRACTURING INGREDIENTS FOR ALL WELLS TO BE REPORTED TO FRACFOCUS WITHIN 60 DAYS AFTER THE CONCLUSION THE HYDRAULIC FRACTURING OPERATIONS, USING THE FOLLOWING LINK: FRACFOCUS.ORG

SPACING

6/27/2019 - G71 - N/A - DISPOSAL WELL