API NUMBER: 049 25406

OKLAHOMA CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION P.O. BOX 52000 OKLAHOMA CITY, OK 73152-2000 (Rule 165:10-3-1)

Approval Date: 02/10/2023
Expiration Date: 08/10/2024

Horizontal Hole Oil & Gas

PERMIT TO DRILL

WELL LOCATION: Section: 22 Township: 3N Range: 4W Cou	unty: GARVIN
SPOT LOCATION: SE NW NE NW FEET FROM QUARTER: FROM NO	RTH FROM WEST
SECTION LINES: 352	2 1782
Lease Name: PERCHERON 0304 Well No: 15-	4SH Well will be 352 feet from nearest unit or lease boundary.
Operator Name: RIMROCK RESOURCE OPERATING LLC Telephone: 918	33014714 OTC/OCC Number: 23802 0
RIMROCK RESOURCE OPERATING LLC	HUNGRY HOLLOW, LLC
20 E 5TH ST STE 1300	P.O. BOX 294
TULSA, OK 74103-4462	LINDSAY OK 73052
Formation(s) (Permit Valid for Listed Formations Only):	
Name Code Depth	
1 MISSISSIPPIAN 359MSSP 13500	
Spacing Orders: 659325 Location Exception	Orders: 728170 Increased Density Orders: 727853
Pending CD Numbers: No Pending Working interest	t owners' notified: *** Special Orders: No Special
•	
Total Depth: 18825 Ground Elevation: 1148 Surface Cas	
	Deep surface casing has been approved
Under Federal Jurisdiction: No	Approved Method for disposal of Drilling Fluids:
Fresh Water Supply Well Drilled: No	D. One time land application (REQUIRES PERMIT) PERMIT NO: 23-38853
Surface Water used to Drill: Yes	H. (Other) SEE MEMO
PIT 1 INFORMATION	Category of Pit: C
Type of Pit System: CLOSED Closed System Means Steel Pits	Liner not required for Category: C
Type of Mud System: WATER BASED	Pit Location is: BED AQUIFER
Chlorides Max: 5000 Average: 3000	Pit Location Formation: DUNCAN
Is depth to top of ground water greater than 10ft below base of pit? Y	
Within 1 mile of municipal water well? N	
Wellhead Protection Area? N	
Wellhead Protection Area? N Pit <u>is</u> located in a Hydrologically Sensitive Area.	
	Category of Pit: C
Pit <u>is</u> located in a Hydrologically Sensitive Area.	Category of Pit: C Liner not required for Category: C
Pit <u>is</u> located in a Hydrologically Sensitive Area. PIT 2 INFORMATION Type of Pit System: CLOSED Closed System Means Steel Pits Type of Mud System: OIL BASED	
Pit <u>is</u> located in a Hydrologically Sensitive Area. PIT 2 INFORMATION Type of Pit System: CLOSED Closed System Means Steel Pits Type of Mud System: OIL BASED Chlorides Max: 300000 Average: 200000	Liner not required for Category: C
Pit <u>is</u> located in a Hydrologically Sensitive Area. PIT 2 INFORMATION Type of Pit System: CLOSED Closed System Means Steel Pits Type of Mud System: OIL BASED Chlorides Max: 300000 Average: 200000 Is depth to top of ground water greater than 10ft below base of pit? Y	Liner not required for Category: C Pit Location is: BED AQUIFER
Pit <u>is</u> located in a Hydrologically Sensitive Area. PIT 2 INFORMATION Type of Pit System: CLOSED Closed System Means Steel Pits Type of Mud System: OIL BASED Chlorides Max: 300000 Average: 200000 Is depth to top of ground water greater than 10ft below base of pit? Y Within 1 mile of municipal water well? N	Liner not required for Category: C Pit Location is: BED AQUIFER
Pit <u>is</u> located in a Hydrologically Sensitive Area. PIT 2 INFORMATION Type of Pit System: CLOSED Closed System Means Steel Pits Type of Mud System: OIL BASED Chlorides Max: 300000 Average: 200000 Is depth to top of ground water greater than 10ft below base of pit? Y	Liner not required for Category: C Pit Location is: BED AQUIFER

HORIZONTAL HOLE 1

SPACING - 659325

Section: 15 Township: 3N Range: 4W Meridian: IM Total Length: 5046

County: GARVIN Measured Total Depth: 18825
Spot Location of End Point: N2 NE NW NW True Vertical Depth: 14000

Feet From: NORTH

1/4 Section Line: 65

End Point Location from
Lease,Unit, or Property Line: 65

NOTES:	
Category	Description
DEEP SURFACE CASING	[2/9/2023 - GC2] - APPROVED; (1) NOTIFY OCC FIELD INSPECTOR IMMEDIATELY OF ANY LOSS OF CIRCULATION OR FAILURE TO CIRCULATE CEMENT TO SURFACE ON ANY CONDUCTOR OR SURFACE CASING. (2) SUBSEQUENT WELLS ON SAME PAD WILL NOT BE ALLOWED DEEP SURFACE CASING IN THE EVENT OF ANY LOSS OF CIRCULATION OR FAILURE TO CIRCULATE CEMENT TO SURFACE ON ANY CONDUCTOR OR SURFACE CASING.
HYDRAULIC FRACTURING	[2/9/2023 - GC2] - OCC 165:10-3-10 REQUIRES:
	1) NOTICE SHALL BE GIVEN AT LEAST 5 BUSINESS DAYS PRIOR TO COMMENCEMENT OF HYDRAULIC FRACTURING OPERATIONS ON A HORIZONTAL WELL TO OPERATORS PRODUCING WELLS WITHIN 1 MILE OF THE COMPLETION INTERVAL OF THE SUBJECT WELL. THE NOTICE TO SUCH OPERATORS SHALL CONTAIN THE INFORMATION IN FORM 6000NOO. IF THE HYDRAULIC FRACTURING OPERATIONS SCHEDULE CHANGES AFTER NOTICE HAS BEEN PROVIDED, RESULTING IN A DELAY OF OPERATIONS OF MORE THAN 5 DAYS FROM THE INITIAL NOTICE, NEW NOTICE IS REQUIRED TO BE GIVEN;
	2) NOTICE WILL BE GIVEN TO THE OCC CENTRAL OFFICE AND LOCAL DISTRICT OFFICES AT LEAST 48 HOURS PRIOR TO COMMENCEMENT OF FRACTURING OPERATIONS. FORM 6000NHF SHALL BE FOUND HERE: HTTPS://OKLAHOMA.GOV/OCC/DIVISIONS/OIL-GAS/OGCD-FORMS; AND,
	3) THE CHEMICAL DISCLOSURE OF HYDRAULIC FRACTURING INGREDIENTS FOR ALL WELLS IS TO BE REPORTED TO FRACFOCUS WITHIN 60 DAYS AFTER THE CONCLUSION OF HYDRAULIC FRACTURING OPERATIONS, FOUND AT FRACFOCUS.ORG
INCREASED DENSITY - 727853	[2/10/2023 - G56] - 15-3N-4W X659325 MSSP 3 WELLS RIMROCK RESOURCES OP, LLC 8/24/2022
LOCATION EXCEPTION - 728170	[2/10/2023 - G56] - (I.O.) 15-3N-4W X659325 MSSP COMPL INT NCT 165' FNL, NCT 165' FSL, NCT 990' FWL RIMROCK RESOURCE OP, LLC 9/6/2022
MEMO	[2/9/2023 - GC2] - CLOSED SYSTEM=STEEL PITS PER OPERATOR REQUEST, OBM RETURNED TO

VENDOR, CUTTINGS PERMITTED PER DISTRICT

[2/10/2023 - G56] - (640)(HOR) 15-3N-4W EXT 617886 MSSP, OTHERS COMPL. INT. NLT 660' FB