

PIT 2 INFORMATION Type of Pit System: CLOSED Closed System Means Steel Pits Type of Mud System: OIL BASED Chlorides Max: 300000 Average: 200000 Is depth to top of ground water greater than 10ft below base of pit? Y Within 1 mile of municipal water well? N Wellhead Protection Area? N Pit is not located in a Hydrologically Sensitive Area. Category of Pit: C Liner not required for Category: C

Pit Location is NON HSA
Pit Location Formation: CHICKASHA

## HORIZONTAL HOLE 1

Sec 03 Twp 15N Rge 9W Cour		
Spot Location of End Point: NW NE NE NE Feet From: NORTH 1/4 Section Line: 50		
Feet From: EAST 1/4 Section Line:	632	
Depth of Deviation: 9103		
Radius of Turn: 477		
Direction: 15		
Total Length: 9786		
Measured Total Depth: 19640		
True Vertical Depth: 10058		
End Point Location from Lease,		
Unit, or Property Line: 50		
Notes:		
Category	Description	
DEEP SURFACE CASING	4/15/2019 - G71 - APPROVED; NOTIFY OCC FIELD INSPECTOR IMMEDIATELY OF ANY LOSS OF CIRCULATION OR FAILURE TO CIRCULATE CEMENT TO SURFACE ON ANY CONDUCTOR OR SURFACE CASING	
HYDRAULIC FRACTURING	4/15/2019 - G71 - OCC 165:10-3-10 REQUIRES:	
	1) PRIOR TO COMMENCEMENT OF HYDRAULIC FRACTURING OPERATIONS FOR HORIZONTAL WELLS, NOTICE GIVEN FIVE BUSINESS DAYS IN ADVANCE TO OFFSET OPERATORS WITH WELLS COMPLETED IN THE SAME COMMON SOURCE OF SUPPLY WITHIN 1/2 MILE;	
	2) WITH NOTICE ALSO GIVEN 48 HOURS IN ADVANCE OF HYDRAULIC FRACTURING ALL WELLS TO BOTH THE OCC CENTRAL OFFICE AND LOCAL DISTRICT OFFICES, USING THE "FRAC NOTICE FORM" FOUND AT THE FOLLOWING LINK: OCCEWEB.COM/OG/OGFORMS.HTML; AND,	
	3) THE CHEMICAL DISCLOSURE OF HYDRAULIC FRACTURING INGREDIENTS FOR ALL WELLS TO BE REPORTED TO FRACFOCUS WITHIN 60 DAYS AFTER THE CONCLUSION THE HYDRAULIC FRACTURING OPERATIONS, USING THE FOLLOWING LINK: FRACFOCUS.ORG	
INCREASED DENSITY - 694266	4/18/2019 - GA8 - 3-15N-9W X659640 MSNLC 4 WELLS DEVON ENERGY PROD. CO., L.P. 4/8/2019	
INCREASED DENSITY - 694267	4/18/2019 - GA8 - 10-15N-9W X659640 MSNLC 4 WELLS DEVON ENERGY PROD. CO., L.P. 4/8/2019	

073 26556 MCCARTHY 10\_3-15N-9W 7HX

Category	Description
INTERMEDIATE CASING	4/15/2019 - G71 - DUE TO THE KNOWN POTENTIAL RISK OF ENCOUNTERING AN OVER- PRESSURED ZONE IN THE MORROW SERIES IN THIS AREA, THE TECHNICAL MANAGER RECOMMENDS SETTING AN INTERMEDIATE STRING OF CASING IMMEDIATELY ABOVE THE MORROW SERIES
MEMO	4/15/2019 - G71 - PITS 1 & 2 - CLOSED SYSTEM=STEEL PITS PER OPERATOR REQUEST, PIT 2 - OBM RETURNED TO VENDOR, CUTTINGS PERMITTED PER DISTRICT
PENDING CD - 201901012	4/18/2019 - GA8 - (I.O.) 10 & 3-15N-9W EST MULTIUNIT HORIZONTAL WELL X659640 MSNLC, WDFD 10 & 3-15N-9W (WDFD ADJACENT COMMON SOURCE OF SUPPLY TO MSNLC) 50% 10-15N-9W 50% 3-15N-9W DEVON ENERGY PROD. CO., L.P. REC 3/12/2019 (MILLER)
PENDING CD - 201901013	4/18/2019 - GA8 - (I.O.) 10 & 3-15N-9W X659640 MSNLC, WDFD 10 & 3-15N-9W X165:10-3-28(C)(2)(B) MAY BE CLOSER THAN 600' TO ERNESTINE 3-A & MCCARTHY 10-3-15N- 9W 3HX COMPL. INT. (10-15N-9W) NCT 165' FSL, NCT 0' FNL, NCT 330' FEL COMPL. INT. (3-15N-9W) NCT 0' FSL, NCT 165' FNL, NCT 330' FEL DEVON ENERGY PROD. CO., L.P. REC 3/12/2019 (MILLER)
SPACING - 659640	4/18/2019 - GA8 - (640)(HOR) 10 & 3-15N-9W EXT 652808 WDFD EST MSNLC POE TO BHL (WDFD) NCT 165' FNL & FSL, NCT 330' FEL & FWL POE TO BHL (MSNLC) NCT 660' FB (COEXIST SP. ORDER #308002 MSSD)