API NUMBER: 019 26537

OKLAHOMA CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION P.O. BOX 52000 OKLAHOMA CITY, OK 73152-2000 (Rule 165:10-3-1)

Approval Date: 01/24/2023

Expiration Date: 07/24/2024

Straight Hole Oil & Gas

## **PERMIT TO DRILL**

WELL LOCATION: Section: 27 Township: 4S Range: 2W	County: CARTER	
SPOT LOCATION: NE NE NW NW FEET FROM QUARTER: FROM	M NORTH FROM WEST	
SECTION LINES.	206 1027	
Lease Name: HHU Well N	No: 534 Well will be 206 feet from nearest unit or lease boundary.	
Operator Name: KODIAK OIL & GAS INC Telephor	ne: 9407594001 OTC/OCC Number: 23226 0	
KODIAK OIL & GAS INC	RANDY K AND LAURA A SMITH	
204 N WALNUT ST	11787 MEMORIAL RD	
MUENSTER, TX 76252-2766	WILSON OK 73463	
Formation(s) (Permit Valid for Listed Formations Only):		
Name Code Depth		
1 HOXBAR 405HXBR 1800		
Spacing Orders: 63637 Location Exc	ception Orders: No Exceptions Increased Density Orders: No Density	
Pending CD Numbers: No Pending Working interest owners' notified: *** Special Orders: No Special		
Total Depth: 2800 Ground Elevation: 912 Surface Casing: 0 Depth to base of Treatable Water-Bearing FM: 540		
Alternate Casing Program		
Cement will be circulated by use of a two-stage cementing tool from 640 to 0 .		
Under Federal Jurisdiction: No	Approved Method for disposal of Drilling Fluids:	
Fresh Water Supply Well Drilled: No	D. One time land application (REQUIRES PERMIT) PERMIT NO: 23-38837	
Surface Water used to Drill: Yes	H. (Other) CBL REQUIRED	
PIT 1 INFORMATION	Category of Pit: 2	
Type of Pit System: ON SITE	Liner not required for Category: 2	
Type of Mud System: WATER BASED	Pit Location is: BED AQUIFER	
Chlorides Max: 5000 Average: 3000	Pit Location Formation: WELLINGTON	
Is depth to top of ground water greater than 10ft below base of pit? Y		
Within 1 mile of municipal water well? N		
Wellhead Protection Area? N		
Pit <u>is</u> located in a Hydrologically Sensitive Area.		

NOTES:

Category	Description
ALTERNATE CASING	[1/24/2023 - GC2] - APPROVED; (1) MUD UP PRIOR TO TD TO PROTECT SHALLOW SANDS, (2) 2-STAGE CEMENTING TOOL TO BE SET AT 100' BELOW BTW, (3) COPY OF CBL NEEDS TO BE SUBMITTED TO THE TECHNICAL STAFF IMMEDIATELY, & (4) SUBSEQUENT WELLS ON SAME PAD WILL NOT BE ALLOWED ALTERNATE SURFACE CASING IN THE EVENT OF ANY LOSS OF CIRCULATION OR FAILURE TO CIRCULATE CEMENT TO SURFACE ON ANY CONDUCTOR OR SURFACE CASING. A COMPLETION ATTEMPT, IN CASES WHERE THE PROTECTION OF THE TREATABLE WATER IS QUESTIONABLE, IS STRICTLY PROHIBITED. RULE 165: 10-3-4 (D)(4)(C)
HYDRAULIC FRACTURING	[1/24/2023 - GC2] - OCC 165:10-3-10 REQUIRES:
	1) NOTICE SHALL BE GIVEN AT LEAST 5 BUSINESS DAYS PRIOR TO COMMENCEMENT OF HYDRAULIC FRACTURING OPERATIONS ON A HORIZONTAL WELL TO OPERATORS PRODUCING WELLS WITHIN 1 MILE OF THE COMPLETION INTERVAL OF THE SUBJECT WELL. THE NOTICE TO SUCH OPERATORS SHALL CONTAIN THE INFORMATION IN FORM 6000NOO. IF THE HYDRAULIC FRACTURING OPERATIONS SCHEDULE CHANGES AFTER NOTICE HAS BEEN PROVIDED, RESULTING IN A DELAY OF OPERATIONS OF MORE THAN 5 DAYS FROM THE INITIAL NOTICE, NEW NOTICE IS REQUIRED TO BE GIVEN;
	2) NOTICE WILL BE GIVEN TO THE OCC CENTRAL OFFICE AND LOCAL DISTRICT OFFICES AT LEAST 48 HOURS PRIOR TO COMMENCEMENT OF FRACTURING OPERATIONS. FORM 6000NHF SHALL BE FOUND HERE: HTTPS://OKLAHOMA.GOV/OCC/DIVISIONS/OIL-GAS/OGCD-FORMS; AND,
	3) THE CHEMICAL DISCLOSURE OF HYDRAULIC FRACTURING INGREDIENTS FOR ALL WELLS IS TO BE REPORTED TO FRACFOCUS WITHIN 60 DAYS AFTER THE CONCLUSION OF HYDRAULIC FRACTURING OPERATIONS, FOUND AT FRACFOCUS.ORG
SPACING - 63637	[1/24/2023 - G56] - (UNIT) NW4 NW4 NW4, NE4 NW4 NW4, NW4 NE4 NW4, SE4 NE4 NW4, S2 NW4 NW4, SW4 NE4 NW4, N2 SW4 NW4, NW4 SE4 NW4, SW4 NW4 NE4, N2 SW4 NE4, E2 NW4 NE4 27-4S-2W EST HEWITT HOXBAR UNIT FOR HXBR