

Oklahoma Corporation Commission  
Oil & Gas Conservation Division  
Post Office Box 52000  
Oklahoma City, Oklahoma 73152-2000  
Rule 165: 10-3-25

Form 1002A

API No.: 35061223720000

**Completion Report**

Spud Date: April 26, 2019

OTC Prod. Unit No.: 3506122372

Drilling Finished Date: May 25, 2019

1st Prod Date: September 13, 2019

Completion Date: September 13, 2019

**Amended**

Amend Reason: OCC - CORRECTION FOR FINAL LOC. EXCEPTION ORDERS & MULTIUNIT ORDERS

**Drill Type: HORIZONTAL HOLE**

Well Name: CHIPMUNK 2-30/31H

Purchaser/Measurer: SOUTHWEST ENERGY

Location: HASKELL 30 8N 20E  
NW NW NW NW  
94 FNL 258 FWL of 1/4 SEC  
Latitude: 35.14464469 Longitude: -95.24283966  
Derrick Elevation: 719 Ground Elevation: 696

First Sales Date: 09/13/2019

Operator: TRINITY OPERATING USG LLC 23879

1717 S BOULDER AVE STE 201  
TULSA, OK 74119-4842

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	706365		696441	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9.625	36	J-55	1528		355	SURFACE
PRODUCTION	5.5	20	P-110	17922		1785	4665

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

**Total Depth: 17922**

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
There are no Packer records to display.		There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Oct 02, 2019	WOODFORD			2685		2431	FLOWING		FULL	1110

Completion and Test Data by Producing Formation			
Formation Name: WOODFORD		Code: 319WDFD	Class: GAS
<b>Spacing Orders</b>		<b>Perforated Intervals</b>	
<b>Order No</b>	<b>Unit Size</b>	<b>From</b>	<b>To</b>
660419	640	7519	17758
695455	640		
706364	MULTIUNIT		
<b>Acid Volumes</b>		<b>Fracture Treatments</b>	
69,006 TOTAL GALS ACID		21,786,324 TOTAL GALS SLICKWATER	
		11,129,277 TOTAL LBS SAND	

Formation	Top
ATOKA	1478
SPIRO SANDSTONE	6063
WAPANUCKA LIMESTONE	6166
UNION VALLEY	6282
CROMWELL	6503
JEFFERSON	6766
FALSE CANEY	6821
CANEY	6939
MAYES	7122
WOODFORD	7293

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

<b>Other Remarks</b>
There are no Other Remarks.

Lateral Holes
Sec: 31 TWP: 8N RGE: 20E County: HASKELL
SW SE SE SW
36 FSL 2220 FWL of 1/4 SEC
Depth of Deviation: 6947 Radius of Turn: 374 Direction: 170 Total Length: 10387
Measured Total Depth: 17922 True Vertical Depth: 6877 End Pt. Location From Release, Unit or Property Line: 36

FOR COMMISSION USE ONLY	
Status: Accepted	1144123