

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35087222950000

Completion Report

Spud Date: March 13, 2020

OTC Prod. Unit No.: 087-227031-0-0000

Drilling Finished Date: June 08, 2020

1st Prod Date: December 27, 2020

Completion Date: December 27, 2020

Drill Type: HORIZONTAL HOLE

Min Gas Allowable: Yes

Well Name: INCE 0604 5HW-22X

Purchaser/Measurer: ENABLE

Location: MCCLAIN 27 6N 4W
SW SE SW SW
325 FSL 700 FWL of 1/4 SEC
Latitude: 34.957956 Longitude: -97.615465
Derrick Elevation: 1206 Ground Elevation: 1176

First Sales Date: 12/27/2020

Operator: OVINTIV MID-CONTINENT INC. 20944

4 WATERWAY AVE STE 100
THE WOODLANDS, TX 77380-2764

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	718048		710043	
	Commingled			710045	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	11 3/4	47	J-55	1473		445	SURFACE
PRODUCTION	5 1/2	20	P-110	21145		2565	SURFACE

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 21175

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Jan 17, 2021	WOODFORD	1045	43	1122	1073	1628	FLOWING	4000	30	3770

Completion and Test Data by Producing Formation																
Formation Name: WOODFORD	Code: 319WDFD	Class: OIL														
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center; padding: 5px;">Spacing Orders</th> </tr> </thead> <tbody> <tr> <td style="width: 50%; padding: 5px;">Order No</td> <td style="width: 50%; padding: 5px;">Unit Size</td> </tr> <tr> <td style="padding: 5px;">626773</td> <td style="padding: 5px;">640</td> </tr> <tr> <td style="padding: 5px;">717820</td> <td style="padding: 5px;">MULTIUNIT</td> </tr> </tbody> </table>	Spacing Orders		Order No	Unit Size	626773	640	717820	MULTIUNIT	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center; padding: 5px;">Perforated Intervals</th> </tr> </thead> <tbody> <tr> <td style="width: 50%; padding: 5px;">From</td> <td style="width: 50%; padding: 5px;">To</td> </tr> <tr> <td style="padding: 5px;">11166</td> <td style="padding: 5px;">21078</td> </tr> </tbody> </table>		Perforated Intervals		From	To	11166	21078
Spacing Orders																
Order No	Unit Size															
626773	640															
717820	MULTIUNIT															
Perforated Intervals																
From	To															
11166	21078															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center; padding: 5px;">Acid Volumes</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">NA</td> </tr> </tbody> </table>	Acid Volumes	NA	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center; padding: 5px;">Fracture Treatments</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">TOTAL FLUID - 579,076 BARRELS TOTAL PROPPANT - 25,362,455 POUNDS</td> </tr> </tbody> </table>		Fracture Treatments	TOTAL FLUID - 579,076 BARRELS TOTAL PROPPANT - 25,362,455 POUNDS										
Acid Volumes																
NA																
Fracture Treatments																
TOTAL FLUID - 579,076 BARRELS TOTAL PROPPANT - 25,362,455 POUNDS																

Formation	Top
WOODFORD MD	11043
WOODFORD TVD	10902

Were open hole logs run? No
 Date last log run:

 Were unusual drilling circumstances encountered? No
 Explanation:

Other Remarks
OCC - THE ORDER 717782 DISMISSED THE APPLICATION FOR EXCEPTION TO THE RULE 165:10-3-28.

Lateral Holes
Sec: 22 TWP: 6N RGE: 4W County: MCCLAIN NE NW NW NW 83 FNL 440 FWL of 1/4 SEC Depth of Deviation: 10525 Radius of Turn: 738 Direction: 2 Total Length: 9912 Measured Total Depth: 21175 True Vertical Depth: 10853 End Pt. Location From Release, Unit or Property Line: 83

FOR COMMISSION USE ONLY	
Status: Accepted	1146043