

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35151246070000

Completion Report

Spud Date: November 21, 2022

OTC Prod. Unit No.: 151-230961-0-0000

Drilling Finished Date: December 03, 2022

1st Prod Date: January 04, 2023

Completion Date: January 03, 2023

Drill Type: HORIZONTAL HOLE

Well Name: MACKEY FAMILY 14-29-13 1H

Purchaser/Measurer: TARGA

Location: WOODS 14 29N 13W
SE SE SE SE
170 FSL 215 FEL of 1/4 SEC
Latitude: 36.986211 Longitude: -98.563123
Derrick Elevation: 1344 Ground Elevation: 1323

First Sales Date: 1/4/2023

Operator: BCE-MACH LLC 24174

14201 WIRELESS WAY STE 300
OKLAHOMA CITY, OK 73134-2512

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	732309		There are no Increased Density records to display.	
	Commingle				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13.375	48	J-55	328	500	315	SURFACE
INTERMEDIATE	7	26	P-110	5237	1300	210	1731

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	13	P-110	4192	1000	0	5147	9339

Total Depth: 9354

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
5115	AS1X	There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Jan 24, 2023	MISSISSIPPIAN	64	21	343	5359	1478	GAS LIFT		128	102

Completion and Test Data by Producing Formation			
Formation Name: MISSISSIPPIAN		Code: 359MSSP	Class: OIL
Spacing Orders		Perforated Intervals	
Order No	Unit Size	From	To
728972	640	5237	9354
Acid Volumes		Fracture Treatments	
255 BBLS 15% HCL		31,813 BBLS / 602,800 LBS SAND	

Formation	Top
MISSISSIPPIAN	4847

Were open hole logs run? No
Date last log run:

Were unusual drilling circumstances encountered? No
Explanation:

Other Remarks
OCC: THE OPERATOR REPRESENTED BY AMANDA LAIR STATED THAT THERE WAS NO CEMENT USED FOR THE LINER SPRING BECAUSE IT WAS AN "OH PACKER".

Lateral Holes
Sec: 14 TWP: 29N RGE: 13W County: WOODS NE NW NE NE 51 FNL 662 FEL of 1/4 SEC Depth of Deviation: 4329 Radius of Turn: 646 Direction: 1 Total Length: 4117 Measured Total Depth: 9354 True Vertical Depth: 4846 End Pt. Location From Release, Unit or Property Line: 51

FOR COMMISSION USE ONLY	
Status: Accepted	1149565