

Oklahoma Corporation Commission  
Oil & Gas Conservation Division  
Post Office Box 52000  
Oklahoma City, Oklahoma 73152-2000  
Rule 165: 10-3-25

Form 1002A

API No.: 35151245600000

**Completion Report**

Spud Date: April 03, 2019

OTC Prod. Unit No.: 151-225471-0-0000

Drilling Finished Date: April 21, 2019

1st Prod Date: April 26, 2019

Completion Date: April 26, 2019

**Drill Type: HORIZONTAL HOLE**

Well Name: TOMBERLIN 4-27-14 4H

Purchaser/Measurer: WILLIAMS

Location: WOODS 4 27N 14W  
SE SE SW SW  
270 FSL 1165 FWL of 1/4 SEC  
Latitude: 36.84185782 Longitude: -98.71560482  
Derrick Elevation: 1500 Ground Elevation: 1484

First Sales Date: 4/26/2019

Operator: BCE-MACH LLC 24174

14201 WIRELESS WAY STE 300  
OKLAHOMA CITY, OK 73134-2512

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	693500		693067	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13.375	48	H-40	449		400	SURFACE
INTERMEDIATE	7	26	P-110	5733		220	3068

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	11.6	P-110	4625	0	0	5644	10269

**Total Depth: 10271**

Packer	
Depth	Brand & Type
5395	AS1X

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
May 14, 2019	MISSISSIPPI LIME	57		350	6140	942	GASLIFT			62

**Completion and Test Data by Producing Formation**

Formation Name: MISSISSIPPI LIME

Code:

Class: OIL

**Spacing Orders**

Order No	Unit Size
154482	640

**Perforated Intervals**

From	To
5725	10271

**Acid Volumes**

238 BBLS 15% HCL
------------------

**Fracture Treatments**

33215 BBLS / 589746 LBS
-------------------------

Formation	Top
MISSISSIPPI LIME	5391

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

**Other Remarks**OH PACKER/SLEEVE SYSTEM  
EXCEPTION TO OAC 165:10-3-28**Lateral Holes**

Sec: 4 TWP: 27N RGE: 14W County: WOODS

NE NW NE NW

156 FNL 1967 FWL of 1/4 SEC

Depth of Deviation: 4910 Radius of Turn: 622 Direction: 359 Total Length: 4385

Measured Total Depth: 10271 True Vertical Depth: 5414 End Pt. Location From Release, Unit or Property Line: 156

**FOR COMMISSION USE ONLY**

1143097

Status: Accepted