

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35063248640000

Completion Report

Spud Date: December 06, 2018

OTC Prod. Unit No.: 063-226233-0-0000

Drilling Finished Date: July 15, 2019

1st Prod Date: October 20, 2019

Completion Date: October 13, 2019

Drill Type: HORIZONTAL HOLE

Well Name: LEANN 2-6/7H

Purchaser/Measurer: SOUTHWEST ENERGY

Location: HUGHES 31 8N 12E
SE SE SW SW
286 FSL 1155 FWL of 1/4 SEC
Latitude: 35.11672222 Longitude: -96.08460277
Derrick Elevation: 778 Ground Elevation: 755

First Sales Date: 10/20/2019

Operator: TRINITY OPERATING USG LLC 23879

1717 S BOULDER AVE STE 201
TULSA, OK 74119-4842

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	708895		681045	
	Commingled			708738	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13.375	48	H-40	380		220	SURFACE
INTERMEDIATE	9.625	36	J-55	2788		285	932
PRODUCTION	5.5	20	P-110	15932		1945	1905

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 15970

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Nov 03, 2019	WOODFORD	65	41.5	6785	104384	1488	FLOWING	390	FULL	850

Completion and Test Data by Producing Formation

Formation Name: WOODFORD

Code: 319WDFD

Class: GAS

Spacing Orders

Order No	Unit Size
626376	640
681941	640
708894	MULTIUNIT

Perforated Intervals

From	To
5359	15819

Acid Volumes

39,018 TOTAL GALS ACID

Fracture Treatments

15,749,034 TOTAL SLICKWATER
11,647,950 TOTAL LBS SAND

Formation	Top
BOOCH COAL	2172
MIDDLE BOOCH	2310
LOWER BOOCH	2436
HARTSHORNE	2558
ATOKA	2639
GILCREASE SANSTONE	2981
SPIRO SANDSTONE	3791
WAPANUCKA LIMESTONE	3893
UNION VALLEY	4068
CROMWELL	4115
JEFFERSON	4319
FALSE CANEY	4555
CANEY	4789
MAYES	5068
WOODFORD	5324

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OCC - THE FINAL EXCEPTION TO RULE 165:10-3-28(C)(2)(B) FOR ORDER 692802 WAS DISMISSED BY FINAL ORDER 708434

Lateral Holes

Sec: 7 TWP: 7N RGE: 12E County: HUGHES

SE SW SE SW

44 FSL 1940 FWL of 1/4 SEC

Depth of Deviation: 4785 Radius of Turn: 519 Direction: 175 Total Length: 10369

Measured Total Depth: 15970 True Vertical Depth: 4905 End Pt. Location From Release, Unit or Property Line: 44

FOR COMMISSION USE ONLY

1144171

Status: Accepted