

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35011241750000

Completion Report

Spud Date: March 25, 2019

OTC Prod. Unit No.: 011-225820-0-0000

Drilling Finished Date: May 11, 2019

1st Prod Date: August 07, 2019

Completion Date: July 14, 2019

Drill Type: HORIZONTAL HOLE

Well Name: HAMMERHEAD BIA 20-15N-10W 11MH

Purchaser/Measurer: ANCOVA

Location: BLAINE 29 15N 10W
SW NE NE NE
340 FNL 345 FEL of 1/4 SEC
Latitude: 35.753280225 Longitude: -98.279035567
Derrick Elevation: 1517 Ground Elevation: 1517

First Sales Date: 8/7/2019

Operator: PALOMA OPERATING CO INC 23932

1100 LOUISIANA ST STE 5100
HOUSTON, TX 77002-5220

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
705302	

Increased Density	
Order No	
695506	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13.375	54.5	J-55	1464		875	SURFACE
INTERMEDIATE	9.625	40	P-110	9633		665	6166
PRODUCTION	5.5	23	HCP-110	16479		2150	5875

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 16521

Packer	
Depth	Brand & Type
11276	VS-1X

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Aug 22, 2019	MISSISSIPPIAN	984	51	3072	3121	2049	FLOWING	1050	36/64	1415

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPIAN

Code: 359MSSP

Class: OIL

Spacing Orders

Order No	Unit Size
648300	640

Perforated Intervals

From	To
11470	16358

Acid Volumes

NONE

Fracture Treatments

229,828 BBLs FLUID
11,848,004 LBS PROPPANT

Formation	Top
MERAMEC	10936

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OCC - ORDER 660911 IS A NUNC PRO TUNC TO SPACING ORDER 648300

Lateral Holes

Sec: 20 TWP: 15N RGE: 10W County: BLAINE

NW NE NW NE

65 FNL 1850 FEL of 1/4 SEC

Depth of Deviation: 10695 Radius of Turn: 597 Direction: 358 Total Length: 4888

Measured Total Depth: 16521 True Vertical Depth: 10895 End Pt. Location From Release, Unit or Property Line: 65

FOR COMMISSION USE ONLY

1143395

Status: Accepted