

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35073263110000

Completion Report

Spud Date: October 22, 2018

OTC Prod. Unit No.: 07322452700000

Drilling Finished Date: November 07, 2018

1st Prod Date: December 27, 2018

Completion Date: November 17, 2018

Drill Type: HORIZONTAL HOLE

Well Name: PHYLLIS 36-O2SH

Purchaser/Measurer: MUSTANG

Location: KINGFISHER 36 19N 6W
SE NW NE NW
382 FNL 1805 FWL of 1/4 SEC
Latitude: 36.086054 Longitude: -97.793709
Derrick Elevation: 1147 Ground Elevation: 1127

First Sales Date: 12/27/2018

Operator: SK NEMAHA LLC 24221

11700 KATY FWY STE 900
HOUSTON, TX 77079

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	698656		683702	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9.625	39	J55	336		170	SURFACE
INTERMEDIATE	7	29	P110	6626		415	2465
PRODUCTION	4.5	13.5	P110	11015		415	6150

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 11015

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Jan 09, 2019	OSWEGO	210.1	41.6	764	3633	999	PUMPING		64	291

Completion and Test Data by Producing Formation

Formation Name: OSWEGO

Code: 404OSWG

Class: OIL

Spacing Orders

Order No	Unit Size
645701	640

Perforated Intervals

From	To
10866	6644

Acid Volumes

20% HCL 464BBL, 20% GEL ACID 7398BBL, 20% LIGHT GE

Fracture Treatments

TOTAL FLUID: 56339BBL, NO SAND, TOTAL 15 STAGES

Formation	Top
BIG LIME	6195
OSWEGO	6252

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

PLUG AND PERF COMPLETIONS WITH 15 STAGES

Lateral Holes

Sec: 36 TWP: 19N RGE: 6W County: KINGFISHER

W2 SE SE SW

351 FSL 2291 FWL of 1/4 SEC

Depth of Deviation: 5493 Radius of Turn: 766 Direction: 180 Total Length: 4319

Measured Total Depth: 11015 True Vertical Depth: 6238 End Pt. Location From Release, Unit or Property Line: 351

FOR COMMISSION USE ONLY

1141791

Status: Accepted