

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35003233710000

Completion Report

Spud Date: May 11, 2019

OTC Prod. Unit No.: 003-225717-0-0000

Drilling Finished Date: May 25, 2019

1st Prod Date: June 06, 2019

Completion Date: June 03, 2019

Drill Type: HORIZONTAL HOLE

Well Name: RC BROWN 22-27-11 4H

Purchaser/Measurer: SEMGAS

Location: ALFALFA 22 27N 11W
NW NE NE NW
220 FNL 2180 FWL of 1/4 SEC
Latitude: 36.811188961 Longitude: -98.370395417
Derrick Elevation: 1201 Ground Elevation: 1185

First Sales Date: 06/06/2019

Operator: BCE-MACH LLC 24174

14201 WIRELESS WAY STE 300
OKLAHOMA CITY, OK 73134-2512

Completion Type	
X	Single Zone
	Multiple Zone
	Commingle

Location Exception	
Order No	
703699	

Increased Density	
Order No	
696627	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9.625	36	J-55	428		205	SURFACE
INTERMEDIATE	7	26	P-110	5523		220	2683

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	11.6	P-110	4597	0	0	5444	10041

Total Depth: 10074

Packer	
Depth	Brand & Type
5254	AS1X

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Jun 18, 2019	MISSISSIPPIAN	220	39	562	2554	818	GASLIFT			103

Completion and Test Data by Producing Formation			
Formation Name: MISSISSIPPIAN		Code: 359MSSP	Class: OIL
Spacing Orders		Perforated Intervals	
Order No	Unit Size	From	To
603257	640	5523	10074
Acid Volumes		Fracture Treatments	
238 BBLS 15% HCL		28432 BBLS / 0 LBS	

Formation	Top
MISSISSIPPIAN	5230

Were open hole logs run? No
Date last log run:

Were unusual drilling circumstances encountered? No
Explanation:

Other Remarks
OH PACKER/SLEEVE SYSTEM.

Lateral Holes
Sec: 22 TWP: 27N RGE: 11W County: ALFALFA SW SE SE SW 155 FSL 2210 FWL of 1/4 SEC Depth of Deviation: 4728 Radius of Turn: 376 Direction: 179 Total Length: 4360 Measured Total Depth: 10074 True Vertical Depth: 5316 End Pt. Location From Release, Unit or Property Line: 155

FOR COMMISSION USE ONLY	
Status: Accepted	1143101