

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35051245910000

Completion Report

Spud Date: March 12, 2019

OTC Prod. Unit No.:

Drilling Finished Date: April 06, 2019

1st Prod Date:

Completion Date: April 06, 2019

Drill Type: DIRECTIONAL HOLE

Well Name: JACK SWAGGER 0606 29-1WHR

Purchaser/Measurer:

Location: GRADY 30 6N 6W
NE NE NE NE
225 FNL 178 FEL of 1/4 SEC
Latitude: 34.97074961 Longitude: -97.86497339
Derrick Elevation: 0 Ground Elevation: 0

First Sales Date:

Operator: CAMINO NATURAL RESOURCES LLC 24097

1401 17TH ST STE 1000
DENVER, CO 80202-1247

Completion Type		Location Exception		Increased Density	
	Single Zone	Order No		Order No	
	Multiple Zone	There are no Location Exception records to display.		There are no Increased Density records to display.	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13 3/8	54.5	J-55	1538		1057	SURFACE

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 8210

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
2000	CEMENT
1500	CEMENT
200	CEMENT

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut- In Pressure	Choke Size	Flow Tubing Pressure
There are no Initial Data records to display.										
Completion and Test Data by Producing Formation										
Formation Name: NONECode:Class: PLUG AND ABANDON										
Formation		Top		Were open hole logs run? No Date last log run: Were unusual drilling circumstances encountered? Yes Explanation: AFTER SEVERAL ATTEMPTS WASHING AND REAMING TO THE HOLE PACKING OFF, THE DECISION WAS MADE TO PLUG AND ABANDON THE HOLE.						
Other Remarks										
SET CEMENT PLUG #1 FROM 2,000'-1,500' W/121 BBLs CMT. SET CEMENT PLUG #2 FROM 1,500'-1,000' W/132 BBLs CMT. SET CEMENT PLUG #3 FROM 200'-CELLAR FLOOR W/61 BBL CEMENT. REMOVE CEMENT FROM CELLAR, CUT OFF WELLHEAD, CAP CASING & CUT OFF MOUSE HOLE CONDUCTOR 2' BELOW GL.										
Bottom Holes										
Sec: 20 TWP: 6N RGE: 6W County: GRADY SW SW SW SW 309 FSL 27 FWL of 1/4 SEC Depth of Deviation: 0 Radius of Turn: 0 Direction: 0 Total Length: 0 Measured Total Depth: 8210 True Vertical Depth: 8177 End Pt. Location From Release, Unit or Property Line: 27										
FOR COMMISSION USE ONLY										
Status: Accepted1142927										