

Oklahoma Corporation Commission  
Oil & Gas Conservation Division  
Post Office Box 52000  
Oklahoma City, Oklahoma 73152-2000  
Rule 165: 10-3-25

Form 1002A

API No.: 35003233700000

**Completion Report**

Spud Date: June 13, 2019

OTC Prod. Unit No.: 003-225841-0-0000

Drilling Finished Date: June 28, 2019

1st Prod Date: July 04, 2019

Completion Date: July 02, 2019

**Drill Type: HORIZONTAL HOLE**

Well Name: LEAMON 32-27-11 4H

Purchaser/Measurer: SEMGAS

Location: ALFALFA 32 27N 11W  
NE NW NW NW  
270 FNL 385 FWL of 1/4 SEC  
Latitude: 36.781878695 Longitude: -98.412655944  
Derrick Elevation: 1230 Ground Elevation: 1214

First Sales Date: 07/04/2019

Operator: BCE-MACH LLC 24174

14201 WIRELESS WAY STE 300  
OKLAHOMA CITY, OK 73134-2512

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	705560		695381	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13.375	48	J-55	423		780	SURFACE
INTERMEDIATE	7	26	P-110	5722		220	3074

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	11.6	P-110	4572	0	0	5632	10204

**Total Depth: 10212**

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
5310	AS1X	There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Jul 13, 2019	MISSISSIPPIAN	274		1383	5047	471	GASLIFT			59

Completion and Test Data by Producing Formation			
Formation Name: MISSISSIPPIAN		Code: 359MSSP	Class: OIL
<b>Spacing Orders</b>		<b>Perforated Intervals</b>	
<b>Order No</b>	<b>Unit Size</b>	<b>From</b>	<b>To</b>
593207	640	5717	10212
<b>Acid Volumes</b>		<b>Fracture Treatments</b>	
238 BBLS 15% HCL		32233 BBLS / NO SAND	

Formation	Top
MISSISSIPPIAN	5353

Were open hole logs run? No  
Date last log run:  
  
Were unusual drilling circumstances encountered? No  
Explanation:

Other Remarks
OH PACKER/SLEEVE SYSTEM.

Lateral Holes
Sec: 32 TWP: 27N RGE: 11W County: ALFALFA  SW SE SW SW  150 FSL 657 FWL of 1/4 SEC  Depth of Deviation: 4892 Radius of Turn: 580 Direction: 180 Total Length: 4662  Measured Total Depth: 10212 True Vertical Depth: 5440 End Pt. Location From Release, Unit or Property Line: 150

FOR COMMISSION USE ONLY	
Status: Accepted	1143105