Oklahoma Corporation Commission Oil & Gas Conservation Division Post Office Box 52000 Oklahoma City, Oklahoma 73152-2000

Rule 165: 10-3-25

OTC Prod. Unit No.: 045-227847-0-0000 Drilling Finished Date: April 02, 2022

1st Prod Date: May 11, 2022

Completion Date: May 11, 2022

Drill Type: HORIZONTAL HOLE

Min Gas Allowable: Yes

Well Name: BD 1-29HX Purchaser/Measurer: DCP MIDSTREAM

Location: ELLIS 32 19N 25W First Sales Date: 5/11/2022

S2 N2 NE NE

440 FNL 660 FEL of 1/4 SEC

Latitude: 36.08457 Longitude: -99.88356 Derrick Elevation: 2384 Ground Elevation: 2364

Operator: DUNCAN OIL PROPERTIES INC 15876

100 PARK AVE STE 1200 OKLAHOMA CITY, OK 73102-8023

Completion Type					
Х	Single Zone				
	Multiple Zone				
	Commingled				

Location Exception
Order No
725732

Increased Density					
Order No					
685605					
721159					

Casing and Cement									
Туре	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT		
SURFACE	9 5/8	40	J55	628	500	195	SURFACE		
PRODUCTION	7	29	P110	8407	1630	555	1123		

				Liner				
Туре	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4 1/2	15.1	P110	8324	1400	516	8258	16582

Total Depth: 16602

Packer					
Depth	Brand & Type				
8323	•				

Plug					
Depth Plug Type					
There are no Plug records to display.					

Initial Test Data

August 12, 2022 1 of 2

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut- In Pressure	Choke Size	Flow Tubing Pressure
Jun 11, 2022	CLEVELAND	535	47	1169	2185	625	FLOWING	2317	64/64"	138

Completion and Test Data by Producing Formation

Formation Name: CLEVELAND

Code: 405CLVD

Class: OIL

Spacing Orders					
Order No	Unit Size				
684540	640				
684541	640				
725731	MULTIUNIT				

Perforated Intervals				
From To				
9379	16485			

Acid Volumes

867 BARRELS 15% HCI ACID

Fracture Treatments
3,829,260 POUNDS 30/50 NW SAND
966,040 POUNDS 30/50 RESIN COATED SAND
147,801 BARRELS SLICKWATER

Formation	Тор
CLEVELAND	8664

Were open hole logs run? No Date last log run:

Were unusual drilling circumstances encountered? No Explanation:

Other Remarks

There are no Other Remarks.

Lateral Holes

Sec: 20 TWP: 19N RGE: 25W County: ELLIS

SE NW NE SE

2142 FSL 705 FEL of 1/4 SEC

Depth of Deviation: 8532 Radius of Turn: 536 Direction: 356 Total Length: 8070

Measured Total Depth: 16602 True Vertical Depth: 8957 End Pt. Location From Release, Unit or Property Line: 705

FOR COMMISSION USE ONLY

1148554

Status: Accepted

August 12, 2022 2 of 2