Oklahoma Corporation Commission Oil & Gas Conservation Division Post Office Box 52000 Oklahoma City, Oklahoma 73152-2000

Rule 165: 10-3-25

API No.: 35129241160000 **Completion Report** Spud Date: June 05, 2018

OTC Prod. Unit No.: 129-225091-0-0000 Drilling Finished Date: August 17, 2018

1st Prod Date: December 04, 2018

Amended Completion Date: August 29, 2018

Amend Reason: OCC CORRECTION TO CHANGE CLASSIFICATION TO OIL WELL

Drill Type: HORIZONTAL HOLE

Well Name: SMITH 30X31-16-21 2HC Purchaser/Measurer: BP/ENABLE

ROGER MILLS 19 16N 21W Location:

SE SW SW SE 296 FSL 2220 FEL of 1/4 SEC

Latitude: 35.84194177 Longitude: -99.47173101

Derrick Elevation: 2103 Ground Elevation: 2082

FOURPOINT ENERGY LLC 23429 Operator:

> 100 SAINT PAUL ST STE 400 DENVER, CO 80206-5140

	Completion Type
Х	Single Zone
	Multiple Zone
	Commingled

Location Exception			
Order No			
692310			

Increased Density
Order No
675273

First Sales Date: 12/4/18

Casing and Cement									
Type Size Weight Grade Feet PSI SAX Top of CMT									
SURFACE	13 3/8	54.5	J-55	662	1750	820	SURFACE		
INTERMEDIATE	7	29	HCP-110	8006	3000	401	6802		
PRODUCTION	4 1/2	13.5	P-110	17725	3500	980	13789		

Liner								
Туре	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 19212

Packer					
Depth Brand & Type					
There are no Packer records to display.					

Plug					
Depth Plug Type					
There are no Plug records to display.					

Initial Test Data

June 25, 2020 1 of 2

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut- In Pressure	Choke Size	Flow Tubing Pressure
Mar 15, 2019	TONKAWA	108	41	120	1110	1667	PUMPING	15	64/64	180

Completion and Test Data by Producing Formation

Formation Name: TONKAWA

Code: 406TNKW

Class: OIL

Spacing Orders					
Order No	Unit Size				
657989	640				
134181	640				

Perforated Intervals					
From To					
9210 17531					

Acid Volumes	
72000 GALS FE 15%	

Fracture Treatments				
7880560 LBS COMMON WHITE 100 MESH SAND. 194291 BBLS WATER				

Formation	Тор
TONKAWA	8696

Were open hole logs run? No Date last log run:

Were unusual drilling circumstances encountered? No Explanation:

Other Remarks

There are no Other Remarks.

Lateral Holes

Sec: 31 TWP: 16N RGE: 21W County: ROGER MILLS

SE SW SE SE

200 FSL 694 FEL of 1/4 SEC

Depth of Deviation: 8138 Radius of Turn: 1234 Direction: 179 Total Length: 10075

Measured Total Depth: 19212 True Vertical Depth: 8661 End Pt. Location From Release, Unit or Property Line: 200

FOR COMMISSION USE ONLY

1142226

Status: Accepted

June 25, 2020 2 of 2