

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35047251860000

Completion Report

Spud Date: January 23, 2019

OTC Prod. Unit No.: 04722544100000

Drilling Finished Date: February 04, 2019

1st Prod Date: May 03, 2019

Completion Date: April 17, 2019

Drill Type: HORIZONTAL HOLE

Well Name: BLACKBURN 36-23N-5W 2MH

Purchaser/Measurer:

Location: GARFIELD 25 23N 5W
SE SW SE SW
190 FSL 1700 FWL of 1/4 SEC
Latitude: 36.434449 Longitude: -97.687214
Derrick Elevation: 1203 Ground Elevation: 1180

First Sales Date:

Operator: WHITE STAR PETROLEUM LLC 23358

301 NW 63RD ST STE 600
OKLAHOMA CITY, OK 73116-7906

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	714416		687604	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9-5/8"	36#	J-55	412		200	SURFACE
INTERMEDIATE	7"	26#	P-110	6126		210	2708

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4-1/2"	11.6#	P-110	5015	0	0	5939	10954

Total Depth: 10954

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
May 13, 2019	MISSISSIPPIAN LIME	150	43	136	907	3334				

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPIAN LIME

Code: 351MSSLM

Class: OIL

Spacing Orders

Order No	Unit Size
77383	640

Perforated Intervals

From	To
There are no Perf. Intervals records to display.	

Acid Volumes

NO ACID USED

Fracture Treatments

4,789,480 GAL OF FIGHTR LX-6 WATER.
369,100 LB OF COMMON WHITE 100 MESH.
3,588,300 LB OF PREMIUM WHITE 30/50.

Formation	Top
MISSISSIPPIAN LIME	5857

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OPEN HOLE COMPLETION USING PACKERS AND SLEEVES 6296-10296. TOTAL OF 30 SLEEVES.
BHL FROM PROPOSED PLAT

Lateral Holes

Sec: 36 TWP: 23N RGE: 5W County: GARFIELD

SE SW SE SW

165 FSL 2640 FWL of 1/4 SEC

Depth of Deviation: 5297 Radius of Turn: 766 Direction: 180 Total Length: 4455

Measured Total Depth: 10954 True Vertical Depth: 6074 End Pt. Location From Release, Unit or Property Line: 165

FOR COMMISSION USE ONLY

1142959

Status: Accepted