

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35151245930000

Completion Report

Spud Date: February 28, 2020

OTC Prod. Unit No.: 151-226765-0-0000

Drilling Finished Date: March 11, 2020

1st Prod Date: March 26, 2020

Completion Date: March 18, 2020

Drill Type: HORIZONTAL HOLE

Well Name: ARNDT TRUST 17-28-16 1H

Purchaser/Measurer: SEMGAS

Location: WOODS 8 28N 16W
SE SW SW SW
225 FSL 503 FWL of 1/4 SEC
Latitude: 36.9141329 Longitude: 98.95087816
Derrick Elevation: 1788 Ground Elevation: 1772

First Sales Date: 3-26-2020

Operator: BCE-MACH LLC 24174

14201 WIRELESS WAY STE 300
OKLAHOMA CITY, OK 73134-2512

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	711877		696632	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13.375	48	J-55	567		485	SURFACE
SURFACE	9.625	36	J-55	1491		455	SURFACE
INTERMEDIATE	7	26	P-110	5766		220	2632

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	11.6	P-110	4742	0	0	5650	10392

Total Depth: 10634

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
5447	AS1X	There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Apr 11, 2020	MISSISSIPPI	135	24	1078	7985	667	GASLIFT		128	105

Completion and Test Data by Producing Formation			
Formation Name: MISSISSIPPI		Code: 351MISS	Class: OIL
Spacing Orders		Perforated Intervals	
Order No	Unit Size	From	To
97151	640	5766	10634
Acid Volumes		Fracture Treatments	
262 BBLS 15% HCL		37838 BBLS / 0 LBS SAND	

Formation	Top
MISSISSIPPI	5412

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks
OH PACKER/SLEEVE SYSTEM.

Lateral Holes
Sec: 17 TWP: 28N RGE: 16W County: WOODS SW SE SW SW 154 FSL 666 FWL of 1/4 SEC Depth of Deviation: 4992 Radius of Turn: 594 Direction: 181 Total Length: 4710 Measured Total Depth: 10634 True Vertical Depth: 5482 End Pt. Location From Release, Unit or Property Line: 154

FOR COMMISSION USE ONLY	
Status: Accepted	1145090