

Oklahoma Corporation Commission  
Oil & Gas Conservation Division  
Post Office Box 52000  
Oklahoma City, Oklahoma 73152-2000  
Rule 165: 10-3-25

Form 1002A

API No.: 35043237260000

**Completion Report**

Spud Date: July 29, 2021

OTC Prod. Unit No.: 043-227442

Drilling Finished Date: August 22, 2021

1st Prod Date: October 06, 2021

Completion Date: September 11, 2021

**Drill Type:** HORIZONTAL HOLE

Well Name: SILVER CHARM 1816 1-13H

Purchaser/Measurer: ENABLE

Location: DEWEY 24 18N 16W  
NE NE NW NW  
270 FNL 1120 FWL of 1/4 SEC  
Latitude: 36.0281394 Longitude: -98.86322138  
Derrick Elevation: 1752 Ground Elevation: 1731

First Sales Date: 10/26/21

Operator: BLAKE PRODUCTION COMPANY INC 18119

1601 NW EXPRESSWAY STE 777  
OKLAHOMA CITY, OK 73118-1446

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
722679	

Increased Density	
Order No	
717282	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	10.75	40.5	J55	1994		670	SURFACE
INTERMEDIATE	7 5/8	29.7	P110, L80	9142		370	6647
PRODUCTION	5.5	20	P110	8928		450	8340

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	5	18	P110	4740	0	450	8928	13668

**Total Depth: 13695**

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data
-------------------

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Oct 24, 2021	RED FORK	107	44			241	PUMPING		64	100

Completion and Test Data by Producing Formation

Formation Name: RED FORK

Code: 404RDFK

Class: OIL

Spacing Orders

Order No	Unit Size
126265	640

Perforated Intervals

From	To
9052	13622

Acid Volumes

501 BBLS 7.5% NEFE
--------------------

Fracture Treatments

956590# 100 MESH 4627770# 40/70 MESH 950220# 50/70
--

Formation	Top
HOOVER	5291
ELGIN	5557
HEEBNER	6460
DOUGLAS	6532
LOVELL	6593
TONKAWA	6950
COTTAGE GROVE	7566
OSWEGO	8228
VERDAGRIS	8494
PINK LIME	8609
RED FORK	8691

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OCC: THE PRODUCTION STRING TAPER IS AT 4740'.

Lateral Holes

Sec: 13 TWP: 18N RGE: 16W County: DEWEY

SE NE NW NW

333 FNL 1271 FWL of 1/4 SEC

Depth of Deviation: 8006 Radius of Turn: 840 Direction: 360 Total Length: 4371

Measured Total Depth: 13695 True Vertical Depth: 8641 End Pt. Location From Release, Unit or Property Line: 333

FOR COMMISSION USE ONLY

Status: Accepted

1146901

January 10, 2022

2 of 3

[