

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35073262270001

Completion Report

Spud Date: June 14, 2019

OTC Prod. Unit No.: 073-225976-0-0000

Drilling Finished Date: July 07, 2019

1st Prod Date: August 27, 2019

Completion Date: August 14, 2019

Drill Type: HORIZONTAL HOLE

Well Name: SAND HILLS 25-15N-06W 2MH

Purchaser/Measurer: ANCOVA

Location: KINGFISHER 25 15N 6W
NW NE NE NE
215 FNL 605 FEL of 1/4 SEC
Latitude: 35.75410542 Longitude: -97.782301123
Derrick Elevation: 1194 Ground Elevation: 1174

First Sales Date: 8/27/2019

Operator: PALOMA OPERATING CO INC 23932

1100 LOUISIANA ST STE 5100
HOUSTON, TX 77002-5220

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	705691		704768	
	Commingle				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9.625	36	J-55	1454		430	SURFACE
PRODUCTION	7	29	P-110	7938		310	3685

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	13.5	P-110	5108	0	225	7604	12712

Total Depth: 12730

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
8071	VS-1X	There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Sep 05, 2019	MISSISSIPPIAN	544	39			1826	FLOWING	660	64/64	164

Completion and Test Data by Producing Formation			
Formation Name: MISSISSIPPIAN		Code: 359MSSP	Class: OIL
Spacing Orders		Perforated Intervals	
Order No	Unit Size	From	To
681164	640	8121	12576
Acid Volumes		Fracture Treatments	
NONE		252,199 BBLS FLUID 6,831,351 LBS PROPPANT	

Formation	Top
MERAMEC	7647

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks
There are no Other Remarks.

Lateral Holes
Sec: 25 TWP: 15N RGE: 6W County: KINGFISHER SE SE SE SW 65 FSL 2634 FWL of 1/4 SEC Depth of Deviation: 7609 Radius of Turn: 424 Direction: 183 Total Length: 4455 Measured Total Depth: 12730 True Vertical Depth: 7643 End Pt. Location From Release, Unit or Property Line: 65

FOR COMMISSION USE ONLY	
Status: Accepted	1143660