

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35073265260000

Completion Report

Spud Date: April 09, 2019

OTC Prod. Unit No.: 073-225727-0-0000

Drilling Finished Date: April 18, 2019

1st Prod Date: July 04, 2019

Completion Date: June 17, 2019

Drill Type: HORIZONTAL HOLE

Min Gas Allowable: Yes

Well Name: MOUSE RAT 1605 2-9MH

Purchaser/Measurer:

Location: KINGFISHER 16 16N 5W
NW NW NE NW
249 FNL 1476 FWL of 1/4 SEC
Latitude: 35.870193 Longitude: -97.740313
Derrick Elevation: 1070 Ground Elevation: 1045

First Sales Date:

Operator: OKLAHOMA ENERGY ACQUISITIONS LP 23509

15021 KATY FREEWAY STE 400
HOUSTON, TX 77094-1900

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	689227		687741	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
CONDUCTOR	16"	46#	X-42	110			SURFACE
SURFACE	9-5/8"	36#	J-55	374		265	SURFACE
PRODUCTION	7"	29#	P-110	7334		280	4409

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4-1/2"	13.5#	P-110	5212	0	0	7056	12268

Total Depth: 12270

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
7028	WEATHERFORD AS-III	There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Aug 01, 2019	MISSISSIPPIAN	436	39	1445	3314	426	GAS LIFT		OPEN	179

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPIANCode: 359MSSPClass: OIL

Spacing Orders

Order No	Unit Size
669705	

Perforated Intervals

From	To
There are no Perf. Intervals records to display.	

Acid Volumes

64 BBLS 15% HCL

Fracture Treatments

152,609 BBLS SLICKWATER 3,004,580# SAND PROPPANT

Formation	Top	Were open hole logs run? No Date last log run: Were unusual drilling circumstances encountered? No Explanation:
TOPEKA	4040	
COTTAGE GROVE	5616	
CHECKERBOARD	5975	
OSWEGO	6355	
VERDIGRIS	6540	
PINK LIME	6652	
MISSISSIPPIAN	6815	

Other Remarks

THIS IS AN OPEN HOLE COMPLETION FROM THE BOTTOM OF THE 7" CASING AT 7,830' TO TERMINUS AT 12,270'.
THE 4-1/2" LINER IS NOT CEMENTED.
BHL FROM ITD

Lateral Holes

Sec: 9 TWP: 16N RGE: 5W County: KINGFISHER

NE NE NW NW

171 FNL 1148 FWL of 1/4 SEC

Depth of Deviation: 6628 Radius of Turn: 783 Direction: 360 Total Length: 4412

Measured Total Depth: 12270 True Vertical Depth: 7079 End Pt. Location From Release, Unit or Property Line: 171

FOR COMMISSION USE ONLY

Status: Accepted

1143185