

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35093251610000

Completion Report

Spud Date: September 21, 2018

OTC Prod. Unit No.: 093-224678-0-0000

Drilling Finished Date: October 08, 2018

1st Prod Date: December 05, 2018

Completion Date: October 20, 2018

Drill Type: HORIZONTAL HOLE

Well Name: HD 1-32H

Purchaser/Measurer: TARGA RESOURCES

Location: MAJOR 32 23N 12W
NE NE NW NW
220 FNL 1050 FWL of 1/4 SEC
Latitude: 36.433771 Longitude: -98.511872
Derrick Elevation: 1308 Ground Elevation: 1290

First Sales Date: 12/12/2018

Operator: FAIRWAY RESOURCES OPERATING III LLC 23943

538 SILICON DR STE 101
SOUTHLAKE, TX 76092-7517

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	694971		688758	
	Commingle				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9-5/8	36	J-55	604		270	SURFACE
INTERMEDIATE	7	26	P-110	7250		400	1525

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4-1/2	11.6	P-110	5582	0	305	6727	12309

Total Depth: 12310

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
6705	AS-1X	There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Dec 08, 2018	MISSISSIPPI LIME	166	35.8			3195	PUMPING			163

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPI LIME

Code: 351MSSLM

Class: OIL

Spacing Orders

Order No	Unit Size
689119	640

Perforated Intervals

From	To
7280	12201

Acid Volumes

100,506 GAL OF 15% FE ACID

Fracture Treatments

263,218 BBLS FLUID & 6,544,674 LBS PROPPANT

Formation	Top
MISSISSIPPIAN	6562

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OCC - ORDER 689119 AMENDS SPACING ORDER 55564

Lateral Holes

Sec: 32 TWP: 23N RGE: 12W County: MAJOR

SE SW SW SW

61 FSL 388 FWL of 1/4 SEC

Depth of Deviation: 6630 Radius of Turn: 617 Direction: 183 Total Length: 4710

Measured Total Depth: 12310 True Vertical Depth: 7062 End Pt. Location From Release, Unit or Property Line: 61

FOR COMMISSION USE ONLY

1142480

Status: Accepted