

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35073264280000

Completion Report

Spud Date: March 01, 2019

OTC Prod. Unit No.: 073-225977-0-0000

Drilling Finished Date: March 21, 2019

1st Prod Date: August 31, 2019

Completion Date: August 14, 2019

Drill Type: HORIZONTAL HOLE

Well Name: SAND HILLS 25-15N-6W 3MH

Purchaser/Measurer: ANCOVA

Location: KINGFISHER 24 15N 6W
E2 SW SW SW
330 FSL 415 FWL of 1/4 SEC
Latitude: 35.75561017 Longitude: -97.796780303
Derrick Elevation: 1230 Ground Elevation: 1208

First Sales Date: 8/31/19

Operator: PALOMA OPERATING CO INC 23932

1100 LOUISIANA ST STE 5100
HOUSTON, TX 77002-5220

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	707616		704768	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9.625	36	J-55	1460		421	SURFACE
PRODUCTION	7	29	P-110	7952		234	5696

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	13.5	P-110	5299	0	288	7693	12992

Total Depth: 13007

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
7798	VS-1X	There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Sep 05, 2019	MISSISSIPPIAN	216	39	52	241	1608	FLOWING	1036	64/64	159

Completion and Test Data by Producing Formation			
Formation Name: MISSISSIPPIAN		Code: 359MSSP	Class: OIL
Spacing Orders		Perforated Intervals	
Order No	Unit Size	From	To
681164	640	7848	12897
Acid Volumes		Fracture Treatments	
NONE		208,569 BBLS FLUID 11,343,516 LBS PROPPANT	

Formation	Top
MERAMEC	7389

Were open hole logs run? No
Date last log run:

Were unusual drilling circumstances encountered? No
Explanation:

Other Remarks
There are no Other Remarks.

Lateral Holes
Sec: 25 TWP: 15N RGE: 6W County: KINGFISHER SW SE SW SW 65 FSL 900 FWL of 1/4 SEC Depth of Deviation: 6743 Radius of Turn: 773 Direction: 177 Total Length: 5049 Measured Total Depth: 13007 True Vertical Depth: 7547 End Pt. Location From Release, Unit or Property Line: 65

FOR COMMISSION USE ONLY	
Status: Accepted	1143664