

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35043236700000

Completion Report

Spud Date: December 04, 2018

OTC Prod. Unit No.: 04322509600000

Drilling Finished Date: December 22, 2018

1st Prod Date: March 02, 2019

Completion Date: February 12, 2019

Drill Type: HORIZONTAL HOLE

Min Gas Allowable: Yes

Well Name: SARAH JONES 31-19-14 2H

Purchaser/Measurer: DCP MIDSTREAM

Location: DEWEY 6 18N 14W
NE NW NW NW
210 FNL 525 FWL of 1/4 SEC
Latitude: 36.071776793 Longitude: -98.740847002
Derrick Elevation: 1951 Ground Elevation: 1928

First Sales Date: 3/8/2019

Operator: TAPSTONE ENERGY LLC 23467

100 E MAIN ST
OKLAHOMA CITY, OK 73104-2509

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	697913		687842	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
CONDUCTOR	20	94	H-40	120	100	125	SURFACE
SURFACE	9.625	36	J-55	1509	450	485	SURFACE
PRODUCTION	7	29	P-110	10303	2500	450	4609

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	13.5	P-110	5680	1100	535	9550	15230

Total Depth: 15233

Packer		Plug	
Depth	Brand & Type	Depth	Plug Type
10173	AS1-X	There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Mar 13, 2019	MISSISSIPPIAN LIME	283	44.67	844	2983	1066	FLOWING	1778	31	670

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPIAN LIME

Code: 359PLM

Class: OIL

Spacing Orders

Order No	Unit Size
633539	640

Perforated Intervals

From	To
10311	15135

Acid Volumes

1,836 BBLS

Fracture Treatments

178,769 BBLS WATER 5,857,741 LBS SAND
--

Formation	Top
BASE HEEBNER SHALE	6433
BASE DOUGLAS SAND	6662
TONKAWA SAND	6903
COTTAGE GROVE SAND	7368
HOGSHOOTER	7700
OSWEGO LIME	8136
MORROW SHALE	8824
CHESTER LIME	9066
MANNING	9563
MISSISSIPPIAN LIME	10130
UPPER MERAMEC	10185

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

There are no Other Remarks.

Lateral Holes

Sec: 31 TWP: 19N RGE: 14W County: DEWEY

NE NW NW NW

181 FNL 657 FWL of 1/4 SEC

Depth of Deviation: 9700 Radius of Turn: 392 Direction: 8 Total Length: 4916

Measured Total Depth: 15233 True Vertical Depth: 10043 End Pt. Location From Release, Unit or Property Line: 181

FOR COMMISSION USE ONLY

Status: Accepted

1142526

