

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35093251580000

Completion Report

Spud Date: September 03, 2018

OTC Prod. Unit No.: 093-224536-0-0000

Drilling Finished Date: September 19, 2018

1st Prod Date: October 24, 2018

Completion Date: October 22, 2018

Drill Type: HORIZONTAL HOLE

Well Name: CORNELSON 2-3H

Purchaser/Measurer: TARGA RESOURCES

Location: MAJOR 3 22N 12W
SW SW SW SW
35 FSL 290 FWL of 1/4 SEC
Latitude: 36.405984 Longitude: -98.479323
Derrick Elevation: 1254 Ground Elevation: 1236

First Sales Date: 10/30/2018

Operator: FAIRWAY RESOURCES OPERATING III LLC 23943

538 SILICON DR STE 101
SOUTHLAKE, TX 76092-7517

Completion Type		Location Exception		Increased Density	
X	Single Zone	Order No		Order No	
	Multiple Zone	700976		688740	
	Commingled				

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9-5/8	36	J-55	754		300	SURFACE
PRODUCTION	7	26	P-110	7246		405	1483

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4-1/2	11.6	P-110	5519	0	325	6729	12248

Total Depth: 12248

Packer	
Depth	Brand & Type
6672	AS-1X

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Oct 27, 2018	MISSISSIPPI LIME	349	34			2490	PUMPING			201

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPI LIME

Code: 351MSSLM

Class: OIL

Spacing Orders

Order No	Unit Size
689500	640

Perforated Intervals

From	To
7240	12140

Acid Volumes

100,800 GAL OF 15% FE ACID

Fracture Treatments

263,209 BBLS FLUID 6,671,900 LBS PROPPANT
--

Formation	Top
MISSISSIPPIAN	6008

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OCC - SPACING ORDER 689500 MODIFIES SPACING ORDER 63692

Lateral Holes

Sec: 3 TWP: 22N RGE: 12W County: MAJOR

NE NW NW NW

62 FNL 383 FWL of 1/4 SEC

Depth of Deviation: 6600 Radius of Turn: 663 Direction: 2 Total Length: 4606

Measured Total Depth: 12248 True Vertical Depth: 6933 End Pt. Location From Release, Unit or Property Line: 62

FOR COMMISSION USE ONLY

1141792

Status: Accepted